



# Safety Data Sheet

## Oak and Teak Epoxy Glue (PART A)

SDS Revision Date:  
09/14/2015

### 1. Identification

#### 1.1. Product identifier

**Product Identity** Oak & Teak Epoxy Glue (Part A)  
**Alternate Names** Oak & Teak Epoxy Glue (Part A) Oak & Teak Epoxy Glue (Part A)

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Intended use** See Technical Data Sheet.  
**Application Method** See Technical Data Sheet.

#### 1.3. Details of the supplier of the safety data sheet

**Company Name** Smith & Co.  
5100 Channel Avenue  
Richmond, CA 94804

#### Emergency

**CHEMTREC (USA)** (800) 424-9300  
**24 hour Emergency Telephone No.** Infotrac: 1-800-535-5053  
**Customer Service: Smith & Co.** 510-237-6842

### 2. Hazard(s) identification

#### 2.1. Classification of the substance or mixture

Skin Irrit. 3;H316 Causes mild skin irritation. (Not adopted by US OSHA)  
Eye Dam. 1;H318 Causes serious eye damage.  
Repr. 2;H361 Suspected of damaging fertility or the unborn child.

#### 2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.



**Danger**

H316 Causes mild skin irritation.  
H318 Causes serious eye damage.  
H361 Suspected of damaging fertility or the unborn child.

**[Prevention]:**

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P280 Wear protective gloves / eye protection / face protection.

**[Response]:**

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.  
P308+313 IF exposed or concerned: Get medical advice / attention.  
P310 Immediately call a POISON CENTER or doctor / physician.  
P332+313 If skin irritation occurs: Get medical advice / attention.

**[Storage]:**

P405 Store locked up.

**[Disposal]:**

P501 Dispose of contents / container in accordance with local / national regulations.

### 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Fatty acid polyamides CAS Number: 0068410-23-1	25 - 50	Eye Dam. 1;H318	[1]
p-tert.butyl phenol CAS Number: 0000098-54-4	0.5 – 5.0	Repr. 2;H361 Skin Irrit. 2;H315 Eye Dam. 1;H318	[1]

In accordance with paragraph (i) of §1910.1200, the specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

\*The full texts of the phrases are shown in Section 16.

### 4. First aid measures

#### 4.1. Description of first aid measures

<b>General</b>	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
<b>Inhalation</b>	Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth.
<b>Eyes</b>	Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
<b>Skin</b>	Promptly wash with mild soap and water for at least 15 minutes while removing contaminated clothing and shoes. Launder clothing before reuse and discard contaminated leather articles. Get medical attention if swelling or reddening occurs.
<b>Ingestion</b>	If conscious, give large quantities of water. Do not induce vomiting. Vomiting will cause further damage to the throat. Dilute by giving water or milk to drink if victim is conscious.

# Safety Data Sheet

## Oak and Teak Epoxy Glue (PART A)

SDS Revision Date:  
09/14/2015

Get medical attention immediately. Never give anything by mouth to an unconscious person. Call a physician.

### 4.2. Most important symptoms and effects, both acute and delayed

#### Overview

**SENSITATION:** Prolonged or repeated exposure may cause asthma and skin sensitization or other allergic response.

**OVEREXPOSURE EFFECTS:** Irritation, sensitization and dermatitis.

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:** Allergy, eczema or skin conditions. See section 2 for further details.

#### Eyes

Causes serious eye damage.

#### Skin

Causes mild skin irritation.

## 5. Fire-fighting measures

### 5.1. Extinguishing media

Carbon dioxide, foam, dry chemical

### 5.2. Special hazards arising from the substance or mixture

Decomposition and combustion products may be toxic.

Hazardous decomposition: Decomposition may produce carbon monoxide, carbon dioxide, Aldehydes, oxides of nitrogen.

### 5.3. Advice for fire-fighters

Use self-contained breathing apparatus. Cool fire-exposed containers with water.

ERG Guide No. ----

## 6. Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

Decomposition and combustion products may be toxic.

### 6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

### 6.3. Methods and material for containment and cleaning up

Decomposition and combustion products may be toxic.

Avoid all personal contact. Take up with absorbent material. Shovel into closable containers. Flush contaminated area with water.

## 7. Handling and storage

### 7.1. Precautions for safe handling

See section 2 for further details. - [Prevention]:

### 7.2. Conditions for safe storage, including any incompatibilities

May cause allergic skin reaction.

Avoid contact with eyes, skin or clothing.

Avoid breathing vapor, mist or spray.

Use with good ventilation.

Wash after handling, and before eating, drinking, smoking or using toilet facilities.

Re-seal partly used containers.

Ensure that all containers are properly labeled and/or stored away from children to prevent accidental ingestion.

Store in cool, dry area with adequate ventilation in closed containers, away from open flames and high temperatures.

#### KEEP OUT OF THE REACH OF CHILDREN

Incompatible materials: Incompatible with strong oxidizing agents, mineral acids (E.G. H<sub>2</sub>SO<sub>4</sub>, HCL, HNO<sub>3</sub>, HCLO<sub>4</sub>) and epoxy resins under uncontrolled conditions.

See section 2 for further details. - [Storage]:

### 7.3. Specific end use(s)

No data available.

## 8. Exposure controls and personal protection

### 8.1. Control parameters

#### Exposure

CAS No.	Ingredient	Source	Value
0000098-54-4	p-tert.butyl phenol	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
0068410-23-1	Fatty acid polyamides	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit

#### Carcinogen Data

CAS No.	Ingredient	Source	Value
0000098-54-4	p-tert.butyl phenol	OSHA	Suspect Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0068410-23-1	Fatty acid polyamides	OSHA	Suspect Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

### 8.2. Exposure controls

#### Respiratory

Use NIOSH approved respirator suitable for organic vapors, if required.

#### Eyes

Wear splash-proof chemical goggles or safety spectacles with side shields.

#### Skin

Wear impervious gloves, neoprene or rubber.

#### Engineering Controls

Good general mechanical ventilation and local exhaust.

# Safety Data Sheet

## Oak and Teak Epoxy Glue (PART A)

SDS Revision Date:  
09/14/2015

**Other Work Practices** Wear appropriate equipment to prevent eye or skin contact. Use of barrier cream recommended. Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

### 9. Physical and chemical properties

<b>Appearance</b>	Amber medium-viscosity liquid
<b>Odor</b>	Ammonia
<b>Odor threshold</b>	Not determined
<b>pH</b>	Not Measured
<b>Melting point / freezing point</b>	Not Measured
<b>Initial boiling point and boiling range</b>	>200°C
<b>Flash Point</b>	>200°F
<b>Evaporation rate (Ether = 1)</b>	Not Measured
<b>Flammability (solid, gas)</b>	Not Applicable
<b>Upper/lower flammability or explosive limits</b>	<b>Lower Explosive Limit:</b> Not Measured <b>Upper Explosive Limit:</b> Not Measured
<b>Vapor pressure (Pa)</b>	Not Measured
<b>Vapor Density</b>	Not Measured
<b>Specific Gravity</b>	0.75
<b>Solubility in Water</b>	Insoluble
<b>Partition coefficient n-octanol/water (Log Kow)</b>	Not Measured
<b>Auto-ignition temperature</b>	Not Measured
<b>Decomposition temperature</b>	>200°C
<b>Viscosity (cSt)</b>	Not Measured
<b>9.2. Other information</b>	
No other relevant information.	

### 10. Stability and reactivity

#### 10.1. Reactivity

Hazardous Polymerization will not occur.

#### 10.2. Chemical stability

Stable under normal circumstances.

#### 10.3. Possibility of hazardous reactions

No data available.

#### 10.4. Conditions to avoid

Avoid exposure to elevated temperatures and strong acids or bases in bulk

#### 10.5. Incompatible materials

Incompatible with strong oxidizing agents, mineral acids (E.G. H<sub>2</sub>SO<sub>4</sub>, HCL, HNO<sub>3</sub>, HCLO<sub>4</sub>) and epoxy resins under uncontrolled conditions.

#### 10.6. Hazardous decomposition products

Decomposition may produce carbon monoxide, carbon dioxide, Aldehydes, oxides of nitrogen.

## 11. Toxicological information

### Acute toxicity

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Fatty acid polyamides - (68410-23-1)	No data available	No data available	No data available	No data available	No data available
p-tert.butyl phenol - (98-54-4)	4,000.00, Rat - Category: 5	1,580.00, Mammal - Category: 4	No data available	5.60, Rat - Category: NA	No data available

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	3	Causes mild skin irritation. (Not adopted by US OSHA)
Serious eye damage/irritation	1	Causes serious eye damage.
Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable
Reproductive toxicity	2	Suspected of damaging fertility or the unborn child.
STOT-single exposure	---	Not Applicable
STOT-repeated exposure	---	Not Applicable
Aspiration hazard	---	Not Applicable

# Safety Data Sheet

## Oak and Teak Epoxy Glue (PART A)

SDS Revision Date:  
09/14/2015

### 12. Ecological information

#### 12.1. Toxicity

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and GHS and is not classified as dangerous for the environment, but contains substance(s) dangerous for the environment. See section 3 for details

#### Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Fatty acid polyamides - (68410-23-1)	Not Available	Not Available	Not Available
p-tert.butyl phenol - (98-54-4)	5.14, Pimephales promelas	3.90, Daphnia magna	0.00 (96 hr),

#### 12.2. Persistence and degradability

There is no data available on the preparation itself.

#### 12.3. Bioaccumulative potential

Not Measured

#### 12.4. Mobility in soil

No data available.

#### 12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

#### 12.6. Other adverse effects

No data available.

### 13. Disposal considerations

#### 13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

### 14. Transport information

	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
14.1. UN number	Not Applicable	UN3022	Not Regulated
14.2. UN proper shipping	Not Regulated	Environmentally hazardous	Not Regulated

<b>name</b>	substance, liquid, NOS, (C18) dimer fatty acid (C18) polyamidoamine resin		
<b>14.3. Transport hazard class(es)</b>	<b>DOT Hazard Class:</b> Not Applicable	<b>IMDG:</b> 9	<b>Air Class:</b> Not Applicable
<b>14.4. Packing group</b>	Not Applicable	<b>Sub Class:</b> Not Applicable	
<b>14.5. Environmental hazards</b>		III	Not Applicable
<b>IMDG</b>	Marine Pollutant: Yes		
<b>14.6. Special precautions for user</b>	No further information		

## 15. Regulatory information

<b>Regulatory Overview</b>	The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.		
<b>Toxic Substance Control Act ( TSCA)</b>	All components of this material are either listed or exempt from listing on the TSCA Inventory.		
<b>WHMIS Classification</b>	D2A E		
<b>US EPA Tier II Hazards</b>	<b>Fire:</b> No	<b>Sudden Release of Pressure:</b> No	<b>Reactive:</b> No
	<b>Immediate (Acute):</b> Yes	<b>Delayed (Chronic):</b> No	

**EPCRA 311/312 Chemicals and RQs:**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

**EPCRA 302 Extremely Hazardous:**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

**EPCRA 313 Toxic Chemicals:**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

**Proposition 65 - Carcinogens (>0.0%):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

**Proposition 65 - Developmental Toxins (>0.0%):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

**Proposition 65 - Female Repro Toxins (>0.0%):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

**Proposition 65 - Male Repro Toxins (>0.0%):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

**New Jersey RTK Substances (>1%) :**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

**Pennsylvania RTK Substances (>1%) :**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

## 16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and



# Safety Data Sheet

## Oak and Teak Epoxy Glue (PART A)

SDS Revision Date:  
09/14/2015

orders.

The full text of the phrases appearing in section 3 is:

H315 Causes skin irritation.

H318 Causes serious eye damage.

H361 Suspected of damaging fertility or the unborn child.

**This is the first version in the GHS SDS format. Listings of changes from previous versions in other formats are not applicable.**

The information on this Safety Data Sheet is believed to be accurate and is the best information available to Smith & Company. This document does not purport to be all-inclusive and is intended only as a guide to the appropriate precautions for handling a chemical by a person trained in chemical handling. It does not represent any guarantee of the properties of the product. Smith & CO. makes no warranty of merchantability, fitness for a particular purpose or any other warranty, expressed or implied with respect to such information of the product to which it relates, and we assume no liability resulting from the use or handling of the product to which this SDS relates. Users and handlers of this product should make their own investigations to determine the suitability of the information provided herein for their own purposes.

FOR YOUR PROTECTION:

The continuing decay of our society brings you the following:

The following pertains to all Smith & Co. products, including this one, and any paper upon which this may be printed:

California State Product Liability Warning (Business and Professions Code, Section 1714.45): This product is inherently unsafe. It cannot be made safe.

This was known as the "Willie Brown Law", passed by him in his last days as Speaker of the California legislature, that exempted ordinary consumer products such as butter, eggs tobacco and any other consumer product that wished to be, from product liability suits in the State of California.

California State Health & Safety Code Section 25249.6: All paper products inherently contain detectable levels of formaldehyde. Therefore, under this Code Section and as required by law, it must be stated that detectable amounts of chemicals known to the State of California to cause cancer, birth defects or other reproductive harm may be found in the containers, paper labels or packing materials. This was the result of Proposition 65 in California, some decades back, that sought to define in law, regardless of scientific fact, anything having any hazard at all as having an equal hazard in any lesser concentration, and if it became invisible, it magically ceased to be hazardous at all; bad science, but a California State law ever since.

Revision: 09/14/2015

FOR FURTHER INFORMATION, PLEASE CONTACT: STEVE SMITH

End of Document